

Conductivity Meters

4510 Bench Conductivity/TDS Meter

- Simultaneous display of conductivity or TDS and temperature
- Automatic selection of range for best resolution
- Calibration by cell constant or standard solutions
- Automatic standard recognition
- Storage of up to 32 results
- Bi-directional RS232 link to printer or PC

The 4510 is easy to use but with the flexibility to meet the broadest range of applications and for those where greater accuracy is required the 4510 has automatic conductivity standard recognition and endpoint detection. Set-up options include cell constant, temperature coefficient and reference temperature. The instrument can store up to 32 readings, which can also be sent to a printer or transferred to computer via DataWay and the RS232 interface.

Technical Specification

Conductivity

Range	6 auto-selected from 0 to 1999mS*
Resolution	0.01µS to 1mS
Accuracy	±0.5% ±2 digits
Automatic std. recognition	10µS, 84µS, 1413µS, 12.88mS
Cell constant	0.010 to 19.999

TDS

Range	6 auto-selected from 0-1999g/l*
Resolution	0.01mg/l to 1g/l
Accuracy	±0.5% ±2 digits
EC Ratio	0.50 to 0.80

Temperature

Range	-10 to 105°C
Resolution	0.1°C
Accuracy	±0.5°C
ATC and manual	0 to 100°C
Temperature coefficient	0.00% to 4.00%
Reference temperature	18, 20 or 25°C
Outputs	Analogue and RS232
Connector	7-pin DIN
Power	9V AC ±10% @ 50/60Hz
Size (l x w x d)	210 x 250 x 55mm
Weight	850g

*With k=10 cell

Ordering Information

Part Code	Description
451 001	4510 conductivity meter supplied with glass conductivity probe with ATC (K=1) (027 013), electrode holder and UK power supply



4510



4510